


Desktop Single-sided Card Printer

S25



Front end



Top end



Back end

SEAOBY S

Lightweight body, Reliability and Easy-to-Use Consumables

Advanced thermal dye-sublimation printing technology
Continuous printing of cards and time-saving effort
Simple operation interface and easy-to-use
Lightweight and easy to maintain
Low noise in printing process
High Printing Speed Engine

Full panel YMCKO ribbon: 300 prints/roll
1/2 panel ymckO ribbon: 450 prints/roll
Monochrome black ribbon: 100mx60mm, 200mx60mm
Monochrome ribbon(gold/silver/white/red/ blue): 100mx60mm
KO ribbon: 500 prints/roll
UV Ultraviolet Security Ribbon: 100m×60mm

Features

Compact and lightweight body
Support single-sided printing
High Definition Color Printing
Support hand-feeding

Multi-functional option module to support various card printing

Dual interface card encoding module
Contactless ID Card encoding module
UHF chip card encoding module
Magnetic stripe card encoding module



High quality photo processing by Dye sublimation technology



Come with professional printing software

Technical Parameter

Model	S25 / Desktop Single-sided Card Printer
Specifications	244 × 160 × 208 (mm), 3.4Kg
Interfaces	USB2.0
Input Capacity	--
Output Capacity	--
Print Speed	Monochrome printing: 3~5s per card(single-sided); Full-color(YMCKO) printing: 18s per card(single-sided)
Card Material	PVC / Composite PVC / Other material upon request and validation
Power	AC 100~240V, 50/60 Hz, DC 24-25.5V, 2.7 A
Print Dimension	ISO CR80 (53.98mm×85.60mm), edge-to-edge printing
Print Resolution	300dpi × 300dpi, 300dpi × 600dpi, 300dpi × 1200dpi
Memory	128MB
Print Method	Dye sublimation (Direct-to-card)
Card Thickness	0.3-1.05mm
LCM Display	Chinese: 8 characters per line, 2 lines / English: 16 characters per line, 4 lines / Multi-language
Operation System	Driver: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other made-in-China operating system. Development Kit: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other made-in-China Operating System Card Design Software: iCARDE card design software, support Windows XP/7/8/10 operating systems
Warranty	Card printer : 24 months (artificial damage excluded) / Print head: Replace one for free within 1 year (artificial damage excluded)
Operating Condition	1. Regular running temp.: 15°C-30°C(59-86°F), 20%~65% RH non-condensing 2. Lowest / Highest running temp.: 0°C(32°F) / 40°C(104°F), 20%~65% RH non-condensing
Storage Condition	Temp.: -5°C-70°C(23-158°F), 20%~70% RH non-condensing
Certificates	CCC, FCC, CE, ROHS, UKCA

