

STP-GK1800-2P



Size of short faceplate: 4 13/16" (123mm)
Length, 1 1/4" (31.2mm) Width, 1/16" (2mm)
Depth

Size of long faceplate: 7 15/16" (201.6mm)
Length, 1 7/16" (36.5mm) Width, 1/16" (2mm)
Depth

12/24VDC ELECTRIC RELEASE LONG & SHORT FACEPLATE

This ANSI style electric release (strike) offers flexibility being supplied with both long and short face plates and is field selectable for 12v or 24v power and fail-safe or fail-secure operation.

FEATURES

- Ansi style release
- Switchable fail safe / fail secure
- Lip extensions available
- Reversible
- Dual voltage
- 12Vdc current consumption with 250mA current draw
- 24Vdc current consumption with 150mA current draw
- Supplied with both long and short faceplates so suitable for wooden and metal doors
- TIP; Fail safe means when the power is cut the door will open, fail secure means when the power is cut the door will remain shut.

TECHNICAL INFORMATION

- Voltage: 12V or 24Vdc
- Current draw: 250mA @ 12Vdc 150mA @ 24Vdc
- Operating temp: -10°C to 45°C
- Humidity: 0~95%
- Jaw strength: Tested to 900kg
- Durability: Tested to 1 million cycles
- Suitable for indoor use only

RELATED PRODUCTS



STP-CP22



STP-LP025



STP-M/R1/ADJ



STP-NT200-NS

